



J&D Manufacturing



LEADERS IN MOVING THE WORLD'S AIR

PREMIUM WALL MOUNT FAN WITH BRACKET

High Output Performance High Efficiency Air Circulators

J&D Manufacturing's Extreme Air Premium Wall Mount fans are considered the industries best value performance fan. Although they are not as powerful as our Heavy duty series performance fans, they still blow our competition away. The tilting head with a wall mount allows you to direct the high velocity air where you need it most.

When it comes to transferring electrical energy efficiently into air energy for cooling, air recirculation or air movement, J&D Manufacturing is the world leader.

J&D Manufacturing re-circulation fans when applied properly can be used in the following applications:

- Air de-stratification can help reduce heating and cooling bills by up to 25%
- Air exchange when placed in a wall opening or in open sidewall buildings
- Consistent air temperature throughout a room or building
- Heat stress relief indoors and outdoors for young and old
- Surface drying
- People cooling
- Machine/compressor cooling
- High velocity air cooling
- Insect control
- Air curtains



FEATURES

- All Metal Construction with chrome finish, black blade and wall mount
- Aluminum blade increases air flow and motor Life
- 3-Speed pull chain switch
- Adjustable wall mount
- Oscillating and non-oscillating models
- Meets OSHA standards
- Quiet operation
- 12' Grounded 3-prong plug
- Maintenance free, direct drive high efficiency motors have completely sealed ball bearings, UL and ULC certification, built in automatic thermal overload protection, covered by a **Full One Year Warranty.**
- Almost all J&D Manufacturing re-circulation fans can be used with our misting/fogging product line.

Part#	Size	HP	Volt	Amps		HZ	Phs	Spd	CFM	CFM/Watt	Noise	RPM		Drive	Blade	Cord	Color
				Hi/Low	Hi/Low				Hi/Low	Hi/Low	DB	Hi/Low	Low				
Non-oscillating models																	
PW24	24"	1/3	115	2.8/2.4/1.9	60	1	3	7200/6200/5200	32/28/24	62/54	1580/1240/830	DD	3-painted	12'	Chrome		
PW30	30"	1/3	115	2.8/2.4/1.9	60	1	3	8200/7200/6200	32/28/24	62/54	1580/1240/830	DD	3-painted	12'	Chrome		
Oscillating models																	
PW24OSC	24"	1/3	115	2.8/2.4/1.9	60	1	3	7200/6200/5200	32/28/24	62/54	1580/1240/830	DD	3-painted	12'	Chrome		
PW30OSC	30"	1/3	115	2.8/2.4/1.9	60	1	3	8200/7200/6200	32/28/24	62/54	1580/1240/830	DD	3-painted	12'	Chrome		
DD-Direct Drive																	