

with  
**EC MOTORS**  
for energy savings

# A2X/EC SERIES SPUN ALUMINUM EXHAUSTERS



UPBLAST MODEL

Ideal for exhausting air from restaurants, offices, warehouses or commercial buildings. The A2X series spun aluminum exhaust fan can be used as either a roof top or wall mount exhaust fan.

## FEATURES

- New low profile design
- Sizes, 10" to 15" with more to follow soon
- Newly designed inlet, wheels improving performance up to 30% by size
- Available with high efficiency EC direct drive motors.
- Roof Exhaust - wall mountable
- Now UL762 approved with guard



Canarm certifies that the A2X Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.

## SPECIFICATIONS

### A2X UPBLAST, DIRECT DRIVE WITH EC MOTOR - PSC MODELS WILL VARY

MODEL	MODEL with EC Motor	MAX RPM	MAX HP	0	0.125	0.25	0.5	0.75	1	1.25	1.5
A2X105-UD	A2X105-UD033EC	1800	1/3	1276	1221	1166	1043	890	680	-	-
A2X120-UD	A2X120-UD033EC	1550	1/3	1744	1670	1595	1429	1224	945	-	-
A2X120-UD	A2X120-UD050EC	1800	1/2	2026	1961	1897	1764	1615	1430	1204	577
A2X135-UD	A2X135-UD050EC	1200	1/2	1800	1700	1590	1300	925	-	-	-
A2X135-UD	A2X135-UD075EC	1725	3/4	2598	2524	2451	2303	2130	1939	1709	1415
A2X135-UD	A2X135-UD100EC	1800	1	2711	2640	2570	2429	2267	2100	1884	1631
A2X150-UD	A2X150-UD050EC	1200	1/2	2450	2350	2230	1950	1600	-	-	-
A2X150-UD	A2X150-UD100EC	1625	1	3357	3270	3184	3010	2811	2607	2340	2033

### A2X DOWNBLAST, DIRECT DRIVE WITH EC MOTOR - PSC MODELS WILL VARY


MODEL	MODEL with EC Motor	MAX RPM	MAX HP	0	0.125	0.25	0.5	0.75	1	1.25	1.5
A2X105-DD	A2X105-DD033EC	1800	1/3	1258	1206	1154	1026	868	662	-	-
A2X120-DD	A2X120-DD033EC	1525	1/3	1692	1621	1550	1372	1152	849	-	-
A2X120-DD	A2X120-DD050EC	1750	1/2	1941	1880	1818	1682	1512	1312	1079	-
A2X120-DD	A2X120-DD075EC	1800	3/4	1997	1937	1877	1749	1584	1394	1176	578
A2X135-DD	A2X135-DD050EC	1200	1/2	1760	1675	1560	1275	870	-	-	-
A2X135-DD	A2X135-DD075EC	1725	3/4	2561	2492	2423	2285	2098	1892	1660	1380
A2X135-DD	A2X135-DD100EC	1800	1	2672	2606	2540	2408	2237	2052	1835	1592
A2X150-DD	A2X150-DD050EC	1200	1/2	2444	2333	2223	1939	1579	680	-	-
A2X150-DD	A2X150-DD100EC	1600	1	3259	3176	3093	2900	2700	2450	2205	1895




DOWNBLAST MODEL

## DIMENSIONS



MODEL	WHEEL DIA.	DRIVE	A	B	C	D	E
A2X105	10.5"	DIRECT	19"	13.0"	19.687"	13.125"	19.852"
A2X120	12.25"	DIRECT	19"	13.0"	21.0625"	15.313"	23.160"
A2X135	13.5"	DIRECT	21"	17.25"	23.0625"	16.875"	25.523"
A2X150	15"	DIRECT	21"	17.25"	24.0625"	18.750"	28.359"



UPBLAST



DOWNBLAST



SECTION A-A