

# Blowers

## MODEL ADB – CAST ALUMINUM VOLUME BLOWER – DIRECT DRIVE




### APPLICATION

Designed for use in situations where low volumes of air flow are required at relatively low static pressures. Excellent for removal of welding smoke and fumes and for spot cooling of electronic equipment.

### FEATURES AND BENEFITS

- Cast aluminum spark resistant housings.
- Forward curved squirrel cage type steel wheels provide efficient, quiet performance.
- Round outlets and inlets facilitate connection to standard pipe and duct diameters with slip fit connections or flange to flange.
- Only available in clockwise rotation with four discharge positions available.
- Standard construction meets AMCA Type C spark resistant requirements.
- Suitable for use in airstreams to a maximum of 150°F.



### DIMENSIONS (subject to change without notice)


MODEL	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
ADB-4	4"	4 7/8"	4"	5"	2 3/4"	7"	6 7/8"	4 5/16"	4 1/4"	15/16"	15/16"	5 3/4"	12 1/2"	13 1/8"	9 1/8"
ADB-6	6"	5 7/8"	4 5/8"	5"	4 1/4"	7"	6 7/8"	4 5/16"	4 1/4"	1 1/16"	7/8"	4 1/4"	13 1/2"	14 1/4"	11 3/4"
ADB-8	7 7/8"	7 13/16"	5 3/4"	7 15/16"	5 3/8"	8 1/2"	8 3/8"	6 1/2"	6 1/2"	1 1/8"	15/16"	5 5/8"	17 7/8"	16 5/8"	14"

## MODEL ADB – CAST ALUMINUM VOLUME BLOWER – DIRECT DRIVE PERFORMANCE DATA


MODEL	WHEEL DIA.	RPM	CAPACITY C.F.M.																				
			1/4" SP CFM & BHP		1/2" SP CFM & BHP		3/4" SP CFM & BHP		1" SP CFM & BHP		1-1/2" SP CFM & BHP		2" SP CFM & BHP		2-1/2" SP CFM & BHP		3" SP CFM & BHP		3-1/2" SP CFM & BHP		4" SP CFM & BHP		
ADB4	4-3/4"	1725	210	.035	135	.023	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—		
HADB4	4-3/4"	3450	500	.38	470	.34	440	.32	420	.30	360	.26	260	.16	—	—	—	—	—	—	—	—	
LADB6	6-1/4"	1140	248	.06	96	.02	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
ADB6	6-1/4"	1725	440	.18	370	.14	300	.11	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
HADB6	6-1/4"	3450	900	1.45	870	1.40	850	1.35	820	1.30	780	1.20	730	1.15	660	1.00	580	.90	470	.80	390	.70	
LADB8	8-1/2"	1140	860	.26	720	.18	600	.15	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
ADB8	8-1/2"	1725	1550	1.15	1500	1.05	1490	1.00	1400	.90	1200	.85	950	.70	—	—	—	—	—	—	—	—	—

### OPTIONAL ACCESSORIES


- Cast aluminum inlet or outlet flanges
- Slide gate dampers for inlet or outlet
- Motor weather cover for outdoor service
- Inlet filters
- Inlet and outlet guards




Clockwise Top  
Horizontal  
Discharge



Clockwise  
Down-Blast  
Discharge



Clockwise Bottom  
Horizontal  
Discharge



Clockwise  
Up-Blast  
Discharge