



**\* AVAILABLE IN 3 STANDARD COLORS: BRUSHED SILVER, BLACK, and WHITE**

## MODEL: L SERIES – HI-TECH INDUSTRIAL CEILING FANS

**\* RUGGED, HIGH PERFORMANCE MODEL, ALL METAL HOUSING**

\* FACTORY BALANCED, HEAVY GAUGE POLYPROPYLENE CONTOURED BLADE

**\* VARIABLE SPEED CAPACITOR TYPE, IMPEDANCE PROTECTED, 18 POLE “F” FRAME A/C MOTOR**

\* AVAILABLE IN 3 STANDARD COLORS

**\* MOTOR HAS THERMAL OVERLOAD PROTECTION**

\* (CORD MODELS ONLY, “C” SUFFIX) COMPLETE WITH 6 FT., 120 VOLT GROUNDED CORD

**\* UPPER CANOPY VAULTED STYLE FOR ANGLED CEILINGS**

\* 1” OD X 6” OR 18” STEEL DOWNROD, DRILLED AND CLEVIS PINNED TO MOTOR SHAFT

**\* CSA /US LISTED AND APPROVED, ENERGY STAR RATED**

\* 120 VOLTS / 1 PHASE / 1.2 AMPS

**\* STANDARD WHITE / BLACK / BRUSHED SILVER POWDER COAT**

\* FACTORY INSTALLED TYPE 304 STAINLESS SAFETY CABLE, 7” X 1/16” DIA., 480# BREAKING STRENGTH

**\* 10 YEAR WARRANTY**

**10 YEAR WARRANTY**

## MODEL: CA – INDUSTRIAL CIRCULATING FANS

| MODEL #   | SIZE | AIRFLOW | DOWNROD | CORD/LEADS | MAX RPM | CFM  | COVERAGE | COLOR          |
|-----------|------|---------|---------|------------|---------|------|----------|----------------|
| L-660-6L  | 60”  | DOWN*   | 6”      | LEADS      | 285     | 9630 | 5000     | WHITE          |
| L-660-6C  | 60”  | DOWN    | 6”      | CORD       | 285     | 9630 | 5000     | WHITE          |
| L-660-18L | 60”  | DOWN*   | 18”     | LEADS      | 285     | 9630 | 5000     | WHITE          |
| L-660-18C | 60”  | DOWN    | 18”     | CORD       | 285     | 9630 | 5000     | WHITE          |
| B-660-6L  | 60”  | DOWN*   | 6”      | LEADS      | 285     | 9630 | 5000     | BLACK          |
| B-660-6C  | 60”  | DOWN    | 6”      | CORD       | 285     | 9630 | 5000     | BLACK          |
| B-660-18L | 60”  | DOWN*   | 18”     | LEADS      | 285     | 9630 | 5000     | BLACK          |
| B-660-18C | 60”  | DOWN    | 18”     | CORD       | 285     | 9630 | 5000     | BLACK          |
| S-660-6L  | 60”  | DOWN*   | 6”      | LEADS      | 285     | 9630 | 5000     | BRUSHED SILVER |
| S-660-6C  | 60”  | DOWN    | 6”      | CORD       | 285     | 9630 | 5000     | BRUSHED SILVER |
| S-660-18L | 60”  | DOWN*   | 18”     | LEADS      | 285     | 9630 | 5000     | BRUSHED SILVER |
| S-660-18C | 60”  | DOWN    | 18”     | CORD       | 285     | 9630 | 5000     | BRUSHED SILVER |

**\* WIRE LEAD MODELS MAY BE WIRED FOR REVERSIBILITY (OPTION)**