

These circulators should be used in clean and dry commercial applications - such as schools, shops, offices or warehouses.

## Commercial Circulator

Motor, blades, guards, and mount are packed and shipped in a single UPS-able carton.



## **Features**

- Pull chain switch.
- SJT type 3 conductor, 9' long cord.
- Coated steel guards with retaining clips.
- Steel hub/spider aluminum paddle blades.
- Pole adjusts center of fan from 43" to 60".
- Meets OSHA standards.
- 1 Year limited warranty.

## Motor Specifications

• 1-Phase

• 120V

• 1/4 HP

- 2-Speed
- Ball bearing
- Permanently lubricated
- Open ventilated
- Permanent split capacitor

## Standard Models

UPC# 686334	MODEL	SIZE	MOUNT TYPE	CFM			· AMPS HIGH	WT.	LIST
				HIGH	MED	LOW	AIVIF 3 HIUH	(LBS.)	LIST
870627	CACU 24-P	24"	Pedestal Mount	5400	4900	4300	2.3	63	340
870641	CACU 24-W		Wall Mount					43	290
869744	CACU 30-P	30"	Pedestal Mount	6000	5500	4800	2.4	66	351
870634	CACU 30-W		Wall Mount					46	301

Note: Stocked models may differ in appearance from photograph