

"V SERIES" BELT DRIVEN WALL PANEL EXHAUST FAN



V & RV Series fans are designed with an Automatic Belt Tensioner providing low maintenance and extending the life of the belt and motor

- * High quality heavy duty components are coated with a durable powder coat finish
 - * Single Phase Open Motors
 - * All dual voltage motors are tested and factory wired at 115 volt
 - * Two speed single phase motors available up to 1/2 hp 115V
- Consult factory for price and delivery

SPECIFICATIONS "V" SERIES

BLADE DIA	MODEL NUMBER	VOLTS	HP	SPEED	AMPS	CFM			APPROX WEIGHT	OUTSIDE SQ DIM	DEPTH
						0.0 SP	0.125 SP	0.25 SP			
24"	V 2412 V	115	1/3	1	6.5	3,920	2,070	930	53	30"	
30"	V 3012 V	115	1/3	1	6.5	6,420	4,980	1,790	55	34"	
	V 3013 V	115	1/2	1	11	9,560	7,770	4,850	63		
36"	V 3613 V	115	1/2	1	11	10,900	9,160	4,310	67	40"	16 1/4"
42"	V 4213 V	115	1/2	1	11	14,200	11,600	5,470	87	46"	
48"	V 4813 V	115	1/2	1	11	17,100	11,500	3,900	104	52"	
	V 4814 U	115/230	3/4	1	13/6.5	18,100	13,800	6,370	109		

"RV SERIES" BELT DRIVEN WALL PANEL SUPPLY FAN



SPECIFICATIONS "RV" SERIES

BLADE DIA	MODEL NUMBER	VOLTS	HP	SPEED	AMPS	CFM			APPROX WEIGHT	OUTSIDE SQ DIM	DEPTH
						0.0 SP	0.125 SP	0.25 SP			
24"	RV 2412 V	115	1/3	1	6.5	3,920	2,070	930	53	30"	
30"	RV 3012 V	115	1/3	1	6.5	6,420	4,980	1,790	55	34"	
	RV 3013 V	115	1/2	1	11	9,560	7,770	4,850	63		
36"	RV 3613 V	115	1/2	1	11	10,900	9,160	4,310	67	40"	16 1/4"
42"	RV 4213 V	115	1/2	1	11	14,200	11,600	5,470	87	46"	
48"	RV 4813 V	115	1/2	1	11	17,100	11,500	3,900	104	52"	
	RV 4814 U	115/230	3/4	1	13/6.5	18,100	13,800	6,370	109		

Performance shown is for installation type A: free inlet, free outlet. Performance ratings do not include the effects of accessories.