

## SPECIFICATIONS

Product Description: **8" (20.3 cm) METAL COM-PAX-IAL BLOWER**  
 Part Number: **9537, 9537-15, 9537-25**  
 Style: **AXIAL FAN, DC**

### GENERAL DESCRIPTION:

Lightweight and compact design allows for easy portability without sacrificing performance. Designed to be used with standard car or truck batteries as the source of power. If it is necessary to leave the vehicle running to avoid draining the battery, it is important to ensure that the vehicle is parked downwind from the inlet of the blower to prevent any CO from entering the working area.

### CONSTRUCTION:

- Complete unit epoxy powder coated "safety orange"
- 15-gauge cold rolled steel housing with 18-gauge welded motor mount construction and 20-gauge steel canister
- Available with 15' (4.57m) or 25' (7.62m) ducting and canister
- Enclosed wide base for greater stability
- Steel black powder coated plated grill
- Carry handle made of 3-ply rubber belting
- Equipped with four or five rubber feet

### MOTOR:

HP: 1/4 HP, 12V DC  
 Max RPM: 3800 RPM  
 Current Draw: 22A  
 Fuse: Inline 30A  
 Cord: 15' (4.57m) 12/2 AWG SJTW 90C 300V medium duty, neoprene  
 Connector: Alligator clips

### FAN:

- Glass reinforced polypropylene (PPG) six blade fan
- Aluminum hub
- Moving fan mounted 1 5/8" (4.12cm) from grill for safety

### DUCTING: *(included on 9537-15 and 9537-25 models)*

- Retractable, non-collapsible design, single ply
- PVC coated vinyl and polyester materials, temperature resistant up to 180° F (82.2° C)
- Yellow color with black weather strip and integrated nylon attachment strap
- Class 1 hard drawn spring steel wire helix that meets ASTM 227 specs

### BLOWER DIMENSIONS:

Description	PN	Length	Width	Height	Weight
Blower only	9537	12 1/2" (31.7 cm)	8" (20.3 cm)	10" (25.4 cm)	16 lbs. (7.2 kg)
Blower w/15' Duct Canister	9537-15	28" (71.1 cm)	11" (27.9 cm)	10" (25.4 cm)	31 lbs. (14 kg)
Blower w/25' Duct Canister	9537-25	28" (71.1 cm)	11" (27.9 cm)	10" (25.4 cm)	36 lbs. (16.3 kg)

### FLOW RATES: *(CFM calculated using 15' (4.57 m) of 8" (20.3 cm) ducting)*

Free Air	One 90° Bend	Two 90° Bends
796 CFM (1352.41 m <sup>3</sup> /hr)	667 CFM (1133.24 m <sup>3</sup> /hr)	480 CFM (815.52 m <sup>3</sup> /hr)

