

## SPECIFICATIONS

Product Description:           **DUCTING, STATICALLY CONDUCTIVE, 16" (40.6 cm) DIAMETER**  
 Part Number:                   **9600-15EX, 9600-25EX**  
 Style:                               **RETRACTABLE**

**GENERAL DESCRIPTION:**

This product is lightweight, retractable, and designed for maximum air handling capabilities. Dual direction flow with low friction loss while providing a safe positive means of discharging static build-up.



**CONSTRUCTION:**

- Vinyl and polyester anti-static materials
- Single ply
- Neoprene-coated
- Temp resistant up to -65° F to 250° F (-53° C to 121° C)
- Retractable, Non-collapsible design.
- Class 1 hard drawn spring steel wire helix
- Meets ASTM 227 Specs.
- Meets flame-retardant requirements of UL-94-V0
- Rated to 100,000 OHMS or less per square inch
- Integrated with extended solid grounding wire at each end

**AVAILABLE:**

PN	Diameter	Length	End-Straps
<b>9600-15EX</b>	16" (40.6 cm)	15' (4.57 m)	Dual
<b>9600-25EX</b>	16" (40.6 cm)	25' (7.62 m)	Dual

**ACCESSORIES:**

PN	Ducting Size	Description
<b>9600-01</b>	16" (40.6 cm)	Duct to duct connector, with raised lip
<b>9600-36</b>	16" (40.6 cm)	Storage rack for 16" ducting, up to 25' (7.62 m) ducting
<b>9600-45</b>	16" (40.6 cm)	Duct storage bag
<b>9600-50EX</b>	8" (20.3 cm)	Reducer, statically conductive for 16" (40.6 m) blower to 8" (20.3 m) ducting